

AAPG Drop-In Ceiling Tiles

Wood veneer and high-pressure laminate lay-in ceiling tiles for standard 15/16-inch exposed-tee suspension grids.



AAPG wood-veneer drop-in ceiling tiles in an exposed-tee suspension grid. Product shown for reference; facing, size, and configuration are as specified for each project.

PRODUCT OVERVIEW

AAPG Drop-In Ceiling Tiles are factory-fabricated square lay-in tiles consisting of a wood-fiber substrate faced with wood veneer or high-pressure laminate (HPL). Sized to drop into a nominal 15/16-inch (23.8 mm) exposed-tee suspension grid, they deliver a warm, architectural finish with the accessibility of a standard lay-in ceiling. Available in decorative (non-acoustic) or acoustic (perforated) versions. Reference specification: Section 09 54 26 – Suspended Decorative Ceilings.

Reference standards	ASTM E84
Facing	Wood veneer or high-pressure laminate
Substrate	Wood-fiber core
Suspension grid	15/16" (23.8 mm) exposed tee
Fire performance	Class A (ASTM E84)
Formaldehyde	TSCA Title VI / CARB compliant

TECHNICAL DATA

Characteristic	Technical data
Product	Square lay-in ceiling tiles with a wood-fiber substrate faced with wood veneer or high-pressure laminate.
Facing options	Natural wood veneer or high-pressure decorative laminate (woodgrain, solid color, or custom digital).
Suspension grid	Drops into a nominal 15/16" (23.8 mm) exposed-tee grid; hold-down clips available.
Nominal sizes	24" x 24" (610 x 610 mm) and 24" x 48" (610 x 1219 mm); custom sizes available.
Edge profile	Square lay-in (SLT) standard.
Acoustic option	Perforated tiles with an acoustically transparent backer for sound absorption.
Fire performance	ASTM E84 Class A as required by code and the authority having jurisdiction.
Formaldehyde	TSCA Title VI / CARB-compliant composite core.
Trim & accessories	Hold-down clips, perimeter trim, and matching transitions.
Applications	Lobbies, corridors, conference rooms, and feature ceilings.
Environmental limits	Install in conditioned space at 60–80 °F and 35–55% RH; acclimate prior to installation.
Cleaning	Dust or vacuum; refer to AAPG Care & Maintenance (Wood Veneer or HPL, as applicable).
Reference specification	Section 09 54 26 – Suspended Decorative Ceilings.
Warranty	One (1) year from the date of shipment; refer to AAPG's published warranty for full terms.

Products are fabricated to project drawings. Sizes, colors, finishes, and configurations are as scheduled and detailed for each Project.