

AAPG Flush Wood Doors

Pre-hung interior, exterior, and pocket flush wood door assemblies per WDMA I.S.1-A, with fire- and sound-rated options.



AAPG pre-hung interior and exterior doors. Product shown for reference; facing, core, hardware, and rating are as specified for each project.

PRODUCT OVERVIEW

AAPG is a national supplier and installer of commercial flush wood doors, supplied pre-hung with frames and hardware for interior, exterior, and pocket applications. Doors are available with solid, hollow, mineral (fire-rated), or acoustic cores and with wood-veneer, high-pressure laminate, or factory-primed facings. Many assemblies carry top-tier fire, security, and sound ratings. Reference specification: Section 08 14 16 – Flush Wood Doors.

Reference standards	WDMA I.S.1-A · NFPA 80
Types	Interior, exterior, and pocket
Core	Solid, hollow, mineral (rated), or acoustic
Facing	Wood veneer, HPL, or primed
Fire ratings	20, 45, 60, or 90 minutes
Thickness	1-3/4" (44 mm) standard

TECHNICAL DATA

Characteristic	Technical data
Product	Factory-fabricated flush wood doors, supplied pre-hung with frames and hardware.
Construction	Solid-core or hollow-core flush wood doors complying with WDMA I.S.1-A.
Core options	Particleboard or structural composite lumber (interior); weather-resistant (exterior); mineral (fire-rated); acoustic (sound-rated).
Facing	Wood veneer, high-pressure decorative laminate (HPL), or factory-primed hardboard, as scheduled.
Thickness	1-3/4" (44 mm) standard; 1-3/8" (35 mm) where scheduled.
Fire rating	Labeled mineral-core assemblies rated 20, 45, 60, or 90 minutes per NFPA 80 and UL 10C / NFPA 252.
Sound rating	Acoustic-core assemblies with published STC ratings (ASTM E90 / E413), where scheduled.
Frames	Wood or hollow-metal frames, prepared for hardware, as scheduled.
Hardware	Hinges, locksets, closers, and accessories per the hardware schedule and ANSI/BHMA standards.
Pre-hung assemblies	Door, frame, and hardware factory-assembled into a complete unit ready for installation.
Vision lites & louvers	Factory-installed as scheduled and compatible with the required fire ratings.
Applications	Multi-family, hospitality, commercial, institutional, and healthcare interiors and entrances.
Environmental limits	Store flat in a dry, ventilated space; condition doors to the building environment prior to installation.
Warranty	Manufacturer's standard warranty against defects in materials and workmanship for the applicable door type.

Products are fabricated to project drawings. Sizes, colors, finishes, and configurations are as scheduled and detailed for each Project.